

Enviroguard BT30 Double-Hung Window



**PRECISION
MILLWORKS, INC.**
Specialty Millwork Products

Enviroguard is the NO ROT Alternative to Wood



The BT30 Advantage

- Block and Tackle balance system for ease in operation and durability
- EZ-Tilt latches for convenience in cleaning
- Finger lifts on both sash
- Comes with 4 9/16" standard jamb width. Other jamb widths available upon request
- Window carries a Light Commercial Rating (134 mph)
- Part of a complete line of Enviroguard products, including EG Casements and EG Custom Millwork
- AAMA Certified and NFRC Rated for peace of mind and outstanding energy efficiency
- Coastal version available
- Competitively priced
- Energy Star certified



▲ EZ-Tilt feature for easy cleaning



▲ EZ-Tilt Latch



Enviroguard BT30 Double-Hung Window



**PRECISION
MILLWORKS, INC.**
Specialty Millwork Products

*Enviroguard is the **NO ROT** Alternative to Wood*

The Enviroguard Story

Most people don't worry about the durability of their windows until they have to be replaced due to rot. Now, with the Enviroguard window they won't ever have to. Enviroguard doesn't rot yet it's paintable and has the traditional look of wood.

Enviroguard is a cellular PVC material that is impervious to water and insects. Precision Millworks uses only 100% Enviroguard on the sash, sill and all exterior parts of all its standard sized and custom built windows.

***We call it a technological breakthrough.
You'll recognize it as a smart investment.***

All of our Enviroguard double-hung windows have been structurally tested for wind and water resistance by a nationally certified testing facility. A rating of DP-30 was achieved, which meets or exceeds building code requirements for our market areas.

Finishing

Our Enviroguard double-hung windows come with a primer coat that carries a ten-year warranty. Enviroguard should be painted with standard oil-base or latex paint using industry standard painting techniques after cleaning. **Dark colors (any color that falls within the L value of 56 to 0) should not be used.** L is a measure of the lightness of an object, and ranges from 0 (black) to 100 (white).

Specifications

	Cellular PVC	Pine
Average Density	0.50	0.43
Screw Holding	Face 298# Edge 268#	293# 231#
Water Absorption (%)	≤1.0	15-35

Note: For joining PVC to wood use drywall screws with large thread or flute.

20-10-25 Warranty

We warrant our glass against seal failure for 20 yrs. Our factory-applied primer coating is warranted for 10 years against peeling, flaking or blistering, and our PVC components are warranted against rot, warpage or corrosion for 25 years.

All this adds up to peace of mind for the homeowner!

Size and Arrangements

Size	Rough Opening	Std. Light Arrangement
1/8 x 3/2	22 x 42	4 Over 4
1/8 x 3/10	22 x 50	4 Over 4
1/8 x 4/6	22 x 58	4 Over 4
1/8 x 5/2	22 x 66	4 Over 4
1/8 x 5/6	22 x 70	4 Over 4
1/8 x 6/2	22 x 78	6 Over 6
2/0 x 3/2	26 x 42	4 Over 4
2/0 x 3/10	26 x 50	4 Over 4
2/0 x 4/6	26 x 58	4 Over 4
2/0 x 5/2	26 x 66	4 Over 4
2/0 x 5/6	26 x 70	4 Over 4
2/0 x 6/2	26 x 78	6 Over 6
2/4 x 3/2	30 x 42	6 Over 6
2/4 x 3/10	30 x 50	6 Over 6
2/4 x 4/6	30 x 58	6 Over 6
2/4 x 5/2	30 x 66	6 Over 6
2/4 x 5/6	30 x 70	6 Over 6
2/4 x 6/2	30 x 78	9 Over 9
2/8 x 3/2	34 x 42	6 Over 6
2/8 x 3/10	34 x 50	6 Over 6
2/8 x 4/6	34 x 58	6 Over 6
2/8 x 5/2	34 x 66	6 Over 6
2/8 x 5/6	34 x 70	6 Over 6
2/8 x 6/2	34 x 78	9 Over 9
3/0 x 3/2	38 x 42	6 Over 6
3/0 x 3/10	38 x 50	6 Over 6
3/0 x 4/6	38 x 58	6 Over 6
3/0 x 5/2	38 x 66	6 Over 6
3/0 x 5/6	38 x 70	6 Over 6
3/0 x 6/2	38 x 78	9 Over 9
3/4 x 3/2	42 x 42	8 Over 8
3/4 x 3/10	42 x 50	8 Over 8
3/4 x 4/6	42 x 58	8 Over 8
3/4 x 5/2	42 x 66	8 Over 8
3/4 x 5/6	42 x 70	8 Over 8
3/4 x 6/2	42 x 78	12 Over 12

Precision Millworks, Inc.

910 Dahlonega Highway • Cumming, GA 30040
800-662-7883 • Fax 800-821-3179
770-781-3020 • Fax 770-781-3026
www.norot.com